



## Personal Information

Name: \_\_\_\_\_

Phone Number: \_\_\_\_\_ Email Address: \_\_\_\_\_

7 character password: \_\_\_\_\_  
case sensitive for website order tracking

Authorized Seven Retailer: \_\_\_\_\_

Salesperson: \_\_\_\_\_

## Your Seven Model (please choose one)

- Road**  622 SLX  Elium SLX  Elium SL  
 Axiom SLX  Axiom SL  Axiom S  Axiom
- Cyclocross**  Mudhoney PRO  Mudhoney SLX  Mudhoney SL  Mudhoney S  Mudhoney
- Mixed Terrain**  Evergreen PRO  Evergreen SLX  Evergreen SL  Evergreen S  Evergreen
- Touring**  Expat SL  Expat S  Expat
- Travel**  Airheart PRO  Airheart SLX  Airheart SL  Airheart S  Airheart
- Commuter and Urban**  Cafe Racer SL  Cafe Racer S  Cafe Racer
- Tandem**  Axiom 007 SL  Axiom 007

## Function and Use (please choose one)

Function and Use	Handling	Function and Use	Handling
<input type="checkbox"/> Road Standard	5	<input type="checkbox"/> Triathlon Advanced Position	5
<input type="checkbox"/> Road Performance	6	<input type="checkbox"/> Cyclocross Racing	5
<input type="checkbox"/> Road Endurance	4	<input type="checkbox"/> Cyclocross Expedition	4
<input type="checkbox"/> Light Touring	4	<input type="checkbox"/> Commuting City	5
<input type="checkbox"/> Loaded Touring	3	<input type="checkbox"/> Commuting Rural	4
<input type="checkbox"/> Triathlon Short Course	5	<input type="checkbox"/> Mixed Terrian	4

## Frame Size Information

Top Tube Length:  cm

Head Tube Length:  SSP Std.  Other  Head Tube Extension (cm):  0.0  1.0


Seat Tube Angle:  SSP Std.  Other  Top Tube Slope:  SSP Std.  Other

## Customized Tubeset Details

Average number of miles ridden per week in season:

Age:  Weight:  Gender:  Male  Female

☉ denotes default



## Frame Options

- Wheel Size**  700c  650b  650c
- Toe overlap is acceptable**  Yes  No
- Head Tube**  1-1/8"  44mm
- Rear Axle Spacing**  130  135  
 120  145 (Tandem)
- Bottom Bracket**  Standard Threaded  Eccentric ‡  
 BB30 ‡  PressFit 30 ‡
- Dropouts**  Road, Standard  Track  
 Slider Dropouts ‡

## Brakes

- Road, Standard  Road, Medium Reach (47-57mm)
- V-Brake / Cantilever  Disc Brake, ISO
- Low-Mount Disc Brake, ISO
- Disc brake rotor diameter (mm)  140  160  180  203

## Cable Routing

- Road style: Brake Cable Stops at 7:00 on Top Tube
- Threaded Adjusters on Down Tube at Head Tube
- Cable Stops on Head Tube (default for SLX frames)
- Internal routing for Shimano Di2 - Battery located on:  
 Inside Seat Post  Top of Down Tube  
 Bottom of Down Tube  Underside of Chain Stay
- Internal routing for Campagnolo EPS - Battery located on:  
 Inside Seat Tube  Top of Down Tube  Bottom of Down Tube
- Cyclocross style: all cables on Top of Top Tube

## Frame Options

- Water Bottle Mounts:  0  1  2  3
- Pump Peg  Chain Hanger  Fender Mounts

## Rack Options:

- Rack Mounts:  On Dropouts  On Seat Stays

## Upcharge Options

- S&S BTC™ Couplings ‡  S&S Case Package  Belt Drive Compatible ‡

## Decal Options

Upcharge applies to custom colors. See Brochure for details.

- Black w/ White Outline  Blasted ‡  Other: \_\_\_\_\_

Optional name decal to say: \_\_\_\_\_

- Black  Script lettering  Drive side only
- White  Block lettering  Both sides of top tube

## Paint ‡

Color(s): \_\_\_\_\_

Scheme: \_\_\_\_\_

See examples of Seven's wide range of paint and decals on our website <http://sevencycles.com/paint>. Downloadable templates are available.

## Notes:

\_\_\_\_\_  
\_\_\_\_\_

## Signature

Your signature indicates that all information is true and correct to the best of your knowledge.

## Date

## Services

- Seven's Three-year Protection Plan - \$495**

TYP protects against unforeseen, unlucky, or unfortunate damage to your frame for three years.

## Components Will You be Using

### Fork

- Seven 5E Carbon  Seven CX 'Cross - Canti/V-Brake only
- Seven 5E Medium Reach  Seven 5E 650c
- Fender mounts (not available on Seven 'CX Cross)  No  Yes
- Other Fork (please specify model): \_\_\_\_\_

### Seat Post

- Integrated Seat Post ‡
- Available only on Elium SLX & SL, 622 SLX, Mudhoney SLX & PRO, and Evergreen PRO
- Seven Titanium, Custom Length
- Other:  Set Back  Center Mount

### Stem

- Custom Seven Titanium
- Stem angle:  96°  Other:  Length:
- Stiffness:  S2 Std  S3 Extra Stiff
- Seven Aluminum  Ti bolt upgrade (Aluminum stem only)
- Stem Sourced by retailer: Length: \_\_\_\_\_ Angle: \_\_\_\_\_

### Handlebar

- Seven Aluminum Road Bar Width:  38  40  42  44
- Custom Seven Tiberius Bar\* (Use appropriate Bar order form)
- Bar Sourced by retailer: \_\_\_\_\_

### Spacers

- Seven Titanium Spacers  Aluminum

### Racks

- Custom Seven Rear Rack  Custom Seven Front Rack
- Stainless Steel  Ti  Stainless Steel  Ti

### Seven Component Decal Color

- Silver  Black  Red

### Additional Components

#### Drivetrain

- Geared  Single
- Belt  Internal, please specify: \_\_\_\_\_

Gruppo: \_\_\_\_\_

Crank Set: \_\_\_\_\_  single  double  triple

#### Front Derailleur Mount:

- High Clamp  Low Clamp  None

Tire Width: \_\_\_\_\_

**‡ Upcharge applies to frame. Components and accessories are separate.**



Tel: 617.923.7774

Fax: 617.923.7757

email: [customs@sevencycles.com](mailto:customs@sevencycles.com)